

How to Specify Real Wood Veneers



Wood Veneer Laminate must be Real Wood Veneers LLC.

844-307-9571

RWW #:	_____
Specie:	_____
Size:	48" x 96" usable
Rep/Distributor:	_____

Notes:

REAL WOOD VENEERS' HPL TECHNICAL DATA

Below please find an abbreviated version of our technical data.

USE:

Real Wood Veneers' HPL is recommended for interior use on vertical and light-duty horizontal surfaces. Please contact Real Wood Veneers LLC if you are uncertain about the use of Real Wood Veneers HPL in any application. Caution should be taken on surfaces that may be exposed to harsh chemicals, acidic beverages (alcoholic, colas, etc.) without cleaning the surface for lengthy periods of time.

STORAGE:

Store flat, not on edge. The laminates should be stored face-up in a cool, dry area and in a completely supported flat position. Use a top sheet of chipboard or similar material to hold stored sheets flat. Protect material from twist, rack and edge damage.

SUBSTRATES AND BALANCING SHEETS:

Real Wood Veneers' HPL must be laminated to MDF, HDF, better quality particle-board and very good quality plywood (Baltic Birch, for example). Do not apply directly to gypsum board (sheet rock), concrete or poor quality particle board. Balancing sheets of similar thickness and material are recommended for balanced construction to prevent warping.

REAL WOOD VENEERS' HPL TECHNICAL DATA *CONT.*

PROTECTIVE MASK:

Although Real Wood Veneers' HPL is supplied with a protective mask, care should be taken when handling. Exposure of masked sheets to light or heat for long periods of time may cause problems with the removal of the protective mask. It is recommended to leave this mask on the surface of the laminates during processing work. Additionally, masking tape, for extra protection in routing work, may be applied over the protective mask. Color uniformity and other quality checks should be carried out on the sheets beforehand by lifting up the edge of the mask and laying it back down.

CLEANING AND MAINTENANCE:

Clean with a soft cloth using mild soap and water or nonabrasive glass and metal cleaning liquids. Do not use ammonia, abrasive cleaners or pads, or harsh solvents.

SHIPPING:

Real Wood Veneers' HPL may be rolled for shipping, with limitations. 4' x 8' sheets may be rolled 5 to a carton. 4' x 10' Real Wood Veneers' HPL sheets can be rolled 2 to a carton. We recommend flat packs and skidded crates for larger quantities.

